

PU 2/2 Solenoid Valve (Normal Close)

How to Order?

PU220	--	E1	--	03	--	S	--	T
PU220 Series		Voltage		Port Size		Blank: Standard Type		Blank: DIN Coil
		E1:AC110V		03: 3/8"		S: Small Orifice Type		T: With Timer
		E2:AC220V		04: 1/2"				
		E5:DC12V		06: 3/4"				
		E4:DC24V		08: 1"				

Order example:

* PU220 series, 2 position, 2 port, 3/8" port size, small orifice, Voltage: AC220V, Model: PU220E2-03S

* PU220 series, 2 position, 2 port, 1/2" port size, with Timer, Voltage: DC24V, Model: PU220E4-04T



PU



PUT

Specifications

* With Voltage AC220V

Model	PU220E2-03S	PU220E2-03	PU220E2-04	PU220E2-06	PU220E2-08
	PUT220E2-03S	PUT220E2-03	PUT220E2-04	PUT220E2-06	PUT220E2-08
Working Medium	Air, Water, Oil				
Orifice(mm)	8.0	13	13	20	25
Cv Value	1.00	4.00	4.00	8.60	11.00
Port Size	3/8"	3/8"	1/2"	3/4"	1"
Fluid Viscosity	50 CST				
Working Pressure(Bar)	0-7				
Max. Pressure Resistance(Bar)	11				
Working Temperature Range(°C)	-5~80				