

UD Series 2/2 Solenoid Valve (Normal Close)



UD

How to Order?

UD	-	10	--	E1
UD Series		Port Size		E1: AC110V
UDH: High Pressure		06: 1/8"		E2: AC220V
		08: 1/4"		E3: AC380V
		10: 3/8"		E4: DC24V
				E5: DC12V
				E6: AC36
				E7: AC24V

Order example:

* UD series, 2 position, 2 port, 1/4" port size, orifice 2.5mm, voltage AC220V, Model: UDE2-08

* UDH High Pressure series, 2 position, 2 port, 1/4" port size, orifice 1.2mm, voltage AC220V, Model: UDHE2-08

Specifications

Model	UD-06E2	UD-08E2	UD-10E2	UD-H06E2	UD-H08E2	UD-H10E2
Working Medium	Air, Water, Oil, Gas					
Acting Type	Direct acting					
Type	Normal Close Type					
Orifice(mm)	2.5		4	1.2		2
Cv Value	0.23		0.6	0.05		0.15
Port Size	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"
Fluid Viscosity	20 CST (Below)					

* With Voltage AC220V

Model	UD-06E2	UD-08E2	UD-10E2	UDH-06E2	UDH-08E2	UDH-10E2
Working Pressure(Bar)	0-7			0-20		
Max. Pressure Resistance(Bar)	10			35		
Working Temperature Range(°C)	-5~80					
Voltage Range	± 10%					
Material of Valve Body	-					
Seal Material	NBR, VITON (optional)					