

US Series 2/2 High-Temperature Solenoid Valve (Normal Close)



How to Order?

US	--	10	--	E1	
US Series		Port Size		Voltage	
		10: 3/8"	35: 1-1/4"	E1: AC110V	E5: DC12V
		15: 1/2"	40: 1-1/2"	E2: AC220V	E6: AC36V
		20: 3/4"	50: 2"	E3: AC380V	E7: AC24V
		25: 1"		E4: DC24V	

Order example:

* US series, 2 position, 2 port, 3/8" port size, AC220V, Model: US-10E2

Specifications

* With Voltage AC220V

Model	US-10E2	US-15E2	US-20E2	US-25E2	US-35E2	US-40E2	US-50E2
Working Medium	Air, Water, Steam						
Acting Type	Pilot Type						
Type	Normal Close Type						
Orifice(mm)	17		22		30		50
Cv Value	5		12		20		48
Port Size	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Fluid Viscosity	20 CST (Below)						

Model	US-10E2	US-15E2	US-20E2	US-25E2	US-35E2	US-40E2	US-50E2
Working Pressure(Bar)	1-15						
Max. Pressure Resistance(Bar)	23						
Working Temperature Range(°C)	-5-180						
Voltage Range	± 10%						
Material of Valve Body	Brass						
Seal Material	PTFE						