

UW Series 2/2 Solenoid Valve (Normal Close)

How to Order?

UW	--	06	--	E1
UW Series		Port Size		Voltage
		06: 1/8"	08: 1/4"	E1: AC110V
		10: 3/8"	15: 1/2"	E2: AC220V
		20: 3/4"	25: 1"	E3: AC380V
		35: 1-1/4"	40: 1-1/2"	E4: DC24V
		50: 2"		E5: DC12V
				E6: AC36V
				E7: AC24V



UW

Order example:

* UW series, 2 position, 2 port, 1/2" port size, voltage AC220V, Model: UW-15E2

Specifications

* With Voltage AC220V

Model	UW-10E2	UW-15E2	UW-20E2	UW-25E2	UW-35E2	UW-40E2	UW-50E2
Orifice(mm)	16	16	20	25	35	40	50
Cv Value	5	5	8	12	24	29	48
Port Size	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
Fluid Viscosity	20 CST Below						
Working Pressure(Bar)	Water : 0-5 , Air : 0-7 , Oil : 0-5 , Gas : 0-7						
Max. Pressure Resistance(Bar)	11						
Working Temperature Range(°C)	-5-80						
Voltage Range	± 10%						
Valve Body	Brass						
Seal Material	NBR, VITON (optional)						